OBJECTIVE





Ensure that clear and convenient access for pedestrians is not minimized by vehicular needs.











Increase awareness between pedestrians and motorists.

Maintain the character of a pedestrian friendly street.

OFF-STREET PARKING AND DRIVEWAYS IMPLEMENTATION STRATEGY CHECKLIST


Commercial	Industrial	Public Spaces	Open Spaces	Residential
	© ®	*†*	Îį	A


1	Maintain continuity of the sidewalk.		
2	Locate parking behind buildings rather than directly exposed to the adjacent major street.		
3	Use alleys to access the parking behind the building. If no alley is available, create access to parking from a side street, wherever possible.	==	
4	Accommodate vehicle access to and from the site with as few driveways as possible.		
5	Limit the width of each driveway to the minimum required.		
6	Incorporate architectural features on parking structure facades that respond to the neighborhood context and that contribute to "placemaking".		
7	Limit parking in the front setback of the building to within allowed driveways.		
8	Mitigate the impact of parking visible to the street with the use of planting and landscape walls tall enough to screen headlights.		
9	Illuminate all parking areas and pedestrian walkways.		
10	Reconstruct abandoned driveways as sidewalks.		
11	Reconstruct sub-standard driveways to meet current ADA requirements.		
12	Use architectural features to provide continuity at the street where openings occur due to driveways or other breaks in the sidewalk and building wall.	==	-

1 Maintain continuity of the sidewalk.











2 Locate parking behind buildings rather than directly exposed to the adjacent major street.











Use alleys to access the parking behind the building. If no alley is available, create access to parking from a side street, wherever possible.











4 Accommodate vehicle access to and from the site with as few driveways as possible.











5 Limit the width of each driveway to the minimum required.











Incorporate architectural features on parking structure facades that respond to the neighborhood context and that contribute to "placemaking".











7 Limit parking in the front setback of the building to within allowed driveways.











Mitigate the impact of parking visible to the street with the use of planting and landscape walls tall enough to screen headlights.











9 Illuminate all parking areas and pedestrian walkways.











Reconstruct abandoned driveways as sidewalks.










11 Reconstruct sub-standard driveways to meet current ADA requirements.










Not Recommended



Use architectural features to provide continuity at the street where openings occur due to driveways or other breaks in the sidewalk and building wall.



